



MARINE GENERATORS

4 GSACH V3

Single-Phase

General data

Maximum power*	3.2 kW (3.2 kVA)	Voltage	240 V
Prime Power**	2.9 kW	Amperage	13.3 A
Frequency	60 Hz	Phases	1

Dimensions and weights

Total length without canopy	-	Total length with canopy	590 mm
Total width without canopy	-	Total width with canopy	406 mm
Total height without canopy	-	Total height with canopy	515 mm
Dry weight without canopy	-	Dry weight with canopy	96 Kg

Engine

Base engine manufacturer	Yanmar	Diameter	78 mm (3.07 in)
Model	L70N5	Stroke	67 mm (2.64 in)
Type	Diesel, 4 stroke	Compression ratio	20:1
Engine RPM	3600	Injection system	Mechanical and direct
Number of cylinders	1	Intake system	Naturally aspirated
Total displacement	320 cc	SAE Flywheel housing	-
Oil	SAE 15W40	Coolant capacity	1.2 L (0.32 gal)
Oil capacity	1.2 L (0.32 gal)	Flywheel	-
Power	4.8 kW (6.53 CV)	Coolant flow rate	- (- gal/m)
Salt water flow rate	20 l/min (5.28 gal/m)	Intake air flow rate	0.4 m3/m
Exhaust type	Wet exhaust elbow	V-Belt Protection	-

Rating conditions according to ISO 3046 (100 kPa barometric pressure, 30 % relative humidity abd 25 °C (77 ° F))
* Maximum output power: maximum power supplied by the genset at full load
** Prime Power: rated power according to ISO 3046 and ISO 8528-1. 10 % overload capacity one hour in twelve hours.
Fuel system details
1 kW 1,36 CV 1 kW 1,36 HP (metric) 1 kW 1,36 CH
45580 - 10/24

Fuel system details

Consumption 25%	0.4 l/h (0.11 gal)	Fuel type	Diesel
Consumption 50%	0.7 l/h (0.18 gal)	Fuel standards	Fueloil diesel ASTM
Consumption 75%	1.1 l/h (0.29 gal)	Injection pump type	Individual
Consumption 100%	1.3 l/h (0.34 gal)	Governor type	Mechanical

Electrical system

Battery voltage	12 V	Stop solenoid type	ETS
Starter motor	1.2 kW	Alternator	-
Earth isolated	-	IP 65 box kit	Optional
SCO 11 double panel	Optional	Current transformers	Optional

Installation details

Exhaust hose inner diameter	45 mm (1.77 in)	Maximum fuel lift height	1 m (3.28 ft)
Sea water hose inner diameter	13 mm (0.51 in)	Maximum raw water lift height	1 m (39.37 in)
Fuel feeding hose inner diameter	8 mm (0.31 in)	Maximum sea water temperature	32 ° (89.6 °F)
Fuel return hose inner diameter	8 mm (0.31 in)	Maximum installation angle***	20 °
Minimum battery capacity	12 V 60 Ah		

Alternator details

Brand	MA4	Cos Phi	1
Model	VO90	Tropicalized	Yes
Regulator type	CAPACITOR	Excitation system	Brushless
Number of poles	2	Voltage regulation accuracy**	1
Isolation type*	-	Alternator type	Synchronous
IP protection	-	Standards	EN60034-1, IEC 60034-1, ISO 8528-3

Standard equipment

10 m electrical wiring extension	SCO 5 control panel
Oil extraction pump	Owner´s and alternator manual
Rigid bed	Packaging
Anti Vibration Mounts	

Optional accessories

Siphon break kit mandatory if generator is below waterline	Water Filters
Service/Cruise Kits: fuel and oil filters, raw water pump, impeller, alternator belt,...	Sea water cock
Exhaust System	Welcome Kit

* Other protections available
** With load from 0 to 100%, speed variation from -2% up to +5%, power factor 0,8 linear and balanced load.
*** In all directions
For other requirements please contact the Sales Dept.
45580 - 10/24

SCO 5 Panel



General Description

Graphic LCD with light Display, 128 x 64 pixels
3 LED indicators
Marine genset measures (see display information)
Marine genset protections (see alarm management)
Running hour indicator
Type B USB for programming
Programming from the same panel
Universal Interface
Preheating function
D+ preexcitation terminal
CAN bus output with SAEJ1939 protocol
2 multipurpose timers
Dimensions 118x 108 x 43 mm
Weight 246 g

Alarm Management

Shutdown (SD)
High coolant temperature
Low oil pressure
Overspeed
Overload*
Short circuit*
Overcurrent*
Over/Under voltage
Over/Under frequency
Emergency stop
Warnings (WRN)
Over/Under battery voltage
Maintenance request
Sensor Fails (FLS)

Operating modes

OFF Mode	AUT Mode (auto start/stop engine)
MAN Mode (manual start/stop engine)	

Power Supply

Voltage supply 12/24 DC with fuse protection
Consumption 60/35 mA



Operating Conditions

Operating temperature -20+70 °C
Humidity 95 % without condensation
Front Panel Protection IP65
Standard Conformity
EN 61000-6-2, EN 61000-6-4, EN 61010-1
EN 60068-2-6 (2÷25 Hz / ±1,6 mm; 25÷100 Hz / 4.0 g)
EN 60068-2-30:2005 25/55°C, RH 95%, 48hours
EN 60529 (front panel IP65, back side IP20)

Display Information

Measurement
L1-L3 Voltage (V), Frequency (Hz), Oil Pressure (bar)
Coolant Temperature (°C), Battery voltage (V), RPM
Active Power* (kW), Apparent Power* (kVA), Current* (A), PF*
History log

Dimensions



Detailed drawings, brochures and manuals are available on the web soleadvance.com. All rights reserved.
Technical specifications, data and presentation are subjected to variations, changes and updates without prior notice
Non-contractual information.



Authorized dealer